



T800-Ex FULLY RUGGED TABLET

- 8.1" HD LumiBond® 2.0 display for better viewing experience
- Getac proprietary SnapBack add-on featuring Smart card and contactless RFID reader Combo or 2nd expanded battery
- Choice of 1D/2D imager barcode reader, Serial port, Micro SD or Ethernet
- Up to 10 hours of battery life with one charge. LifeSupport™ battery swappable technology for uninterrupted battery life
- MIL-STD-810G and IP65 certified
- Enhanced Enterprise Security with optional Intel vPro, Windows Disk Encryption, TPM 2.0 and many more multi-factor authentication options.



SnapBack add-on



Specifications

Operating System

Windows 10 Pro

Mobile Computing Platform

Platform Options:

Intel® Atom Processor x7-Z8750 1.6 GHz, burst up to 2.56 GHz
- 2MB Cache

VGA Controller

Intel® HD Graphics

Display

8.1" IPS TFT LCD HD (1280 x 800)
600 nits LumiBond® display with Getac sunlight readable technology

Storage & Memory

4GB LPDDR3 expandable to 8GB
Optional eMMC 64GB / 128GB

Keyboard

6 tablet buttons (Windows, Power, Function Key, Camera Capture/ Barcode Reader Trigger, Volume Up, Volume Down)

Pointing Device

Touchscreen
- Capacitive multi-touch screen
- Optional dual mode touchscreen (multi-touch and digitizer)

Expansion Slot

Optional 1D/2D imager barcode reader

I/O Interface

FHD webcam x 1
8M pixels auto focus rear camera x 1
USB 3.0 (9-pin) x 1
Headphone out/Mic-in Combo x 1
DC in Jack x 1
Micro HDMI x 1

Communication Interface

Intel® Dual Band Wireless-AC 7265, 802.11ac
Bluetooth (v4.0)
Optional dedicated GPS
Optional 4G LTE mobile broadband

Security Feature

TPM 2.0

Power

AC adapter (65W, 100-240VAC, 50 / 60Hz)
Li-Ion battery (7.4V, 4200mAh)

Dimension (W x D x H) & Weight

227 x 151 x 24 mm (8.93" x 5.94" x 0.94")
0.91kg (2 lbs)¹⁾

Rugged Feature

MIL-STD-810G certified and IP65 certified
6 feet drop resistant
Vibration & drop resistant

Environmental Specification

Temperature¹⁾:
- Operating: -21°C to 50°C / -5.8°F to 122°F
- Storage: -51°C to 71°C / -60°F to 160°F
Humidity:
- 95% RH, non-condensing

ATEX / IECEx zone 2/22
II 3G Ex ic IIC T4 Gc
II 3D Ex ic IIIB T130°C Dc

Accessories

Main battery (7.4V, 4200mAh)
2nd expanded battery (14.4V, 2100 mAh)
AC adapter (65W, 100-240VAC)
Capacitive stylus (Hard-tip)
Digitizer pen

Bumper-to-Bumper warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.

That is why Getac has introduced accidental damage as standard under our new Bumper-to-Bumper warranty, to help minimize your enterprise IT costs.

Bumper-to-Bumper is your hassle-free guarantee.

That means you can depend on us to have your unit back in service within days.

Standard

3 years Bumper-to-Bumper.

- i Battery life testing conducted under MobileMark 2007. Battery performance will vary upon software applications, wireless settings, power management settings, LCD brightness, customized modules and environmental conditions. The battery has a limited number of charge cycles and may eventually need to be replaced by a Getac service provider. Battery life and charge cycles vary by use and settings.
- ii Weight and dimensions vary from configurations and optional accessories.
- iii Tested by a national independent third party test lab following MIL-STD-810G.

T800-Ex

Fully Rugged Tablet



Getac

GETAC TECHNOLOGY CORPORATION

5F, Building A, No. 209, Section 1, Nangang Rd.,
Nangang Dist., Taipei City, 11568, Taiwan, R.O.C.
Tel : +886 2 2785 7888
globalmarketing@getac.com | www.getac.com



Copyright © 2018 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved.
Information provided herewith is for reference only,
available specification shall be subjected to quotation by request. V01M02Y18WW


RedLinX[®]
Embedded Solutions
www.redlinx.co.za